



FAYOUM UNIVERSITY
FACULTY OF ENGINEERING
DEPARTMENT OF ELECTRICAL ENGINEERING

Phd Thesis

**MODELING OF HARMONICS PENETRATION,
EFFECTS AND COMPENSATION IN
ELECTRICAL NETWORKS CONSIDERING THE
TIME VARIATION OF LOADS**

A thesis submitted in partial fulfillment of
The requirement for the degree of

Doctor of Philosophy

In

Electrical Engineering

(Electrical Power and Machines)

Submitted by

Khaled Hosny Ibrahiem

Under Supervision of

Prof. Dr. M. B. Magdi Eiteba

Electrical Engineering Department – Faculty of Engineering – Fayoum University

Dr. Saber Mohamed Saleh

Electrical Engineering Department – Faculty of Engineering – Fayoum University

ABSTRACT

Distortion in electric power systems takes place as a direct result of nonlinear nature of electric power system. Beside the problem of harmonic distortion itself, the probabilistic nature of harmonics and system parameters comes to have a considerable impact on the compensator design. Passive compensator sometimes fails to implement its function when the harmonic characteristics widely change.

In this work, studying the effects of the probabilistic nature of harmonics and system parameters (load impedance and harmonic currents) on the system performance and economics is introduced. Designing a multi-step inductive-capacitive compensator based on performance and economic criteria and constraints is also introduced. Finally designing an active power filter based on a new processing algorithm is deduced from the multi-step inductive-capacitive model as the step is too small to be implemented. This thesis uses Genetic Algorithm as an optimization tool in addition to numerical iterative methods.

The contribution of the proposed algorithms is demonstrated in examples taken from previous publications. Finally, simulated results show the following:

- The fixed Inductive-capacitive compensator is not sufficient to ensure satisfactory results in case of probabilistic condition with high variance.
- The multi-step inductive-capacitive compensator provides a considerable improvement in the performance and economics in case of probabilistic condition.
- The new design of active power filter is more economic and robust since no algorithm for harmonic subtraction is needed.