

# **Influence of the Sol–Gel-Derived Nano-Sized TiO<sub>2</sub> and Y<sub>2</sub>O<sub>3</sub> in Improving the Optical and Electric Properties of P(VAc/MMA)**

**S. El-Sayed**, Adel M. El Sayed, Influence of the Sol–Gel-Derived Nano-Sized TiO<sub>2</sub> and Y<sub>2</sub>O<sub>3</sub> in Improving the Optical and Electric Properties of P(VAc/MMA), Brazilian Journal of Physics (2021), doi.org/10.1007/s13538-021-00979-4.

## **Abstract**

Metal oxides (MO)/polymer nanocomposites are attracting more attention due to their low cost and multifunctionality in diverse fields. In this report, two nano-sized MO (TiO<sub>2</sub> and Y<sub>2</sub>O<sub>3</sub>) were prepared by the sol–gel method and dispersed into a biodegradable poly(vinyl acetate)/poly(methyl methacrylate), P(VAc/MMA) blend via the solution casting. The structure, chemical composition, morphology, UV–vis spectra, and dielectric and electrical properties of the prepared samples were studied. XRD and FE-SEM showed the high purity of the prepared cubic TiO<sub>2</sub> nanoparticles (TNp) and Y<sub>2</sub>O<sub>3</sub> nanosheets (YNs). The added MO fillers are well-dispersed inside the polymer blend and influenced its amorphous nature and surface morphology. FTIR spectra indicated a high activity of the nano- fillers towards the surrounding atmosphere, and confirmed the complexation and interaction between fillers and blend functional groups. TNp-doped films exhibited lower transmittance and narrowed the optical bandgap ( $E_g$ ) of the blend from 4.03 to 3.63 eV. The effect of TNp and YNs on the dielectric modulus, ac conductivity ( $\sigma_{ac}$ ), and the blend activation energy ( $E_a$ ) were also discussed. TNp improved the  $\sigma_{ac}$  more effectively from  $1.99 \times 10^{-7}$  to  $6.292 \times 10^{-5}$  S/cm. Moreover, increasing YNs content expanded the time required for the relaxation process. The obtained TNp and their nanocomposite films are suitable for the semiconductor industry and devices.